



Illuminated LED Rescue Sign

Ideal for wall mounting in common rooms and corridor areas

The illuminated banner serves as a visual alarm for gas hazards. In the event of an alarm, the words GASALARM and the pictogram flash. It can be installed both in the hazardous area and in front of the access doors to warn staff in good time. The LED illuminated sign is usually controlled via a potential-free relay contact of the gas warning control panel.

Technical Data

Power supply	24 V DC (230 V AC on request)
Power	6 W
Illuminant	LED
Service life of lamp	approx. 50,000 h
Housing	Polycarbonate white
Protection class	IP 65
Weight approx.	1000 g
Dimensions	H 182 x W 337 x D 75 mm
CE marking	according to EMC and low-voltage directive
Connection cable	NYM 3x1.5 mm ²
Connection	2-pole at 24V (3-pole screw terminal at 230V AC)

HTK Hamburg GmbH
Frahmredder 49 • 22393 Hamburg
Phone: +49 (0)40 - 600 38 38 - 0 • Fax: +49 (0)40 - 600 38 38 - 99
info@htk-hamburg.com



© Copyright 2019 - All contents of this document, in particular Texts, photographs and graphics are protected by copyright. All rights, including reproduction, publication, processing and translation are reserved, HTK Hamburg GmbH. Please contact HTK Hamburg GmbH if you would like to use the contents of this document.

Rev.1_082022_LED-Rescue Sign Gasalarm Wall Mounting_engl • Subject to change without notice